



CS-760B / CS-760W

2-Way Weatherproof Music Horn



Bringing you
high sound quality
under all weather conditions.

The horn speaker that fits all your need
for excellent speech and BGM clarity
in the open...



CS-760B / CS-760W 2-Way Weatherproof Music Horn

- Highly intelligible: suited to voice alarm, public address and BGM application by 2-way speaker system.
- IP66 certified: All weather durability, be it water or dust. Ideal for any fully outdoor applications.
- Special paint coat prevents color degradation, ensuring long-lasting exterior condition.
- Rotary switch facilitates hassle-free impedance change.
- Various mounting brackets available as accessories allowing flexibility of mounting the speaker on a platform, in the ceiling, on the wall or on a pole.

APPLICATION EXAMPLES



Parking spaces



Railway stations



Amusement parks



Sports fields

SPECIFICATIONS

	CS-760B	CS-760W
Rated Input		60W (high impedance)
Rated Impedance		100V Line: 170Ω (60W), 330Ω (30W), 670Ω (15W), 1.3kΩ (7.5W) 70V Line: 83Ω (60W), 170Ω (30W), 330Ω (15W), 670Ω (7.5W)
Sensitivity (1W, 1m)		100dB
Maximum SPL (60W, 1m)		117dB
Frequency Response		100 - 20 kHz
Crossover Frequency		2.5 kHz
Directivity Angle		Horizontal: 90°; Vertical : 80°
Speaker Component		Low Frequency: 16 cm (6") cone-type High Frequency: 2.5 cm (1") dome tweeter
Dust/Water Protection		IP66
Connection		Speaker cord (Hot: Black; Com: White)
Finish	Enclosure: ABS, Black, Paint Coating Punched Net: Surface-treated Steel Plate, Black, Paint Coating Bracket: Stainless Steel, Black, Powder Coating	Enclosure: ABS, White, Paint Coating Punched Net: Surface-treated Steel Plate, White, Paint Coating Bracket: Stainless Steel, White, Powder Coating
Dimensions (W x H x D)		388 x 310 x 367 mm
Weight		7.4kg

 **TOA**
Smiles for the Public

TOA Electronics Pte Ltd

www.toa.com.sg

Specifications are subject to change without notice.
Printed in Singapore (65) 865-1119-04



Like us on Facebook
facebook.com/TOAasiapacific