

SN-U73

UHF PROFESSIONAL WIRELESS MICROPHONE

NTS



2 Channel Quart Control Fixed Frequency SN-U73 HANDHELD

TECHNICAL DATA

Integrative performance

Carrier frequency : UHF 794-806 MHz
Frequency stability : +/-0.005% (-10°C~50°C)
Modulation mode : FM
Max modulation frequency : +/-40KHz
Frequency response : 40Hz~20KHz
Signal/Noise ratio : 100dB
Effective range : 100 m.
Total Harmonic Distortion : ≤ 0.5%
Work temperature : -10°C~50°C

Receiver specification

Receiving mode : Superheterodyne double-conversion
Frequency vibration : PLL lock loop
Sensitivity : -93dBm
Audio output : XLR balance output : 0-400mV
: Phone unbalance output : 0-350mV
Power : 220V/50Hz or 110V/60Hz or DC 15-20V
Rated power : 6W
Rated power consumption : 3W

Transmitter specification

RF output power : ≤ 10 mW
Pickup head : Dynamic cardioid directivity
Batteries : AA 1.5V x 2
Batteries life : up to 6 hours

QUART CONTROL FIXED FREQUENCY



<http://www.nts-solution.com>

All features & specifications are subjected to change without notice.

NTS

บริษัท เอ็นทีเอส อิเล็กทรอนิกส์ โซลูชั่น จำกัด
NTS Electronic Solution Co., Ltd.

1439-1441 ถนนเจริญนคร แขวงบางลำภูล่าง เขตคลองสาน กรุงเทพฯ 10600

โทรศัพท์: 0-2438-7023-4, 0-2437-7639 โทรสาร: 0-2437-1897

<http://www.nts-solution.com> E-mail: nts@nts-solution.com

1439-1441 Charoennakorn Rd. Banglumpoolang Klongsan Bangkok 10600, Thailand

Tel: (+66-2) 438-7023-4, (+66-2) 437-7639 Fax: (+66-2) 437-1897