

DW-240D 2.4GHz Digital Wireless Microphone Systems 32CH



DW-240D (Dual)



Features

- 2.4GHz ISM Digital Wireless Microphone System.
- Digital audio processing technology produces a clear and natural sound.
- Audio Format 16Bit, 38.4kHz
- Pre-Set 32CH (2*16CH) Selectable Frequencies.,Up to 2 simultaneous channels.
- GFSK Modulation.
- No RF Noise.
- IR sync for easy set-up.
- Clear and intuitive LCD display, Status of Frequency AF And RF Signal Etc.
- Up To 30 Meters Line-Of-Sight Range.
- Battery Can Be Used More Than 8 Hours / Lower Battery Consumption.
- Dual receiver system comes with both a handheld microphone and a bodypack transmitter.
- Ideal for Meeting, Training, Conference, karaoke, Clubs,Music Entertainment Etc.
- Optional Hand-Held Microphone, Pocket Transmitter, Lavalier and Headset Available.

Specifications

System

Carrier Frequency	2.404 - 2.474GHz
Available Channels	32CH (2*16CH)
Bandwidth	70MHz
Dynamic Range	85dB
Total Harmonic Distortion	<0.1%

DW-240D : Dual Receiver

Power Supply	DC12V
Consumption Power	2Watts
Signal Noise Ratio	>95dB
Receiving Sensitivity	-80dBm

DW-240HT : Handheld Transmitter

Transmitter RF Output Power	10mW E.I.R.P. maximum
Modulation Type	GFSK
Ultraharmonics	<20dB
Battery Voltage	3V (2×1.5V AA Battery)
Battery Life	Approx 8 Hours

DW-240BT : Body-Pack Transmitter

Transmitter RF Output Power	10mW E.I.R.P. maximum
Modulation Type	GFSK
Ultra-harmonics	<20dB
Battery Voltage	3V (2×1.5V AA Battery)
Battery Life	Approx 8 Hours

Ordering information

- **DW-240D/HT** Dual Handheld wireless microphone set.
Model : **DW-240D/HT**
- **DW-240D/BT** Dual Body pack with combo clip & headworn wireless microphone set.
Model : **DW-240D/BT**

Certifications : CE and RoHS

The DW-240D conforms to standard
ETSI EN 300 440 V2.2.1(2018-07) , ETSI EN 301 489-9 V2.2.0 (2017-03)
IEC 60950-1 , EN 62479: 2010

- Specifications are subject to change without prior notification.