

SU-890D UHF Dual Wireless Microphones Systems 40CH



Features

- UHF 803.3 ~ 805.7MHz Frequency Range. (Brand for Thailand Regulation)
- Frequency Response 30Hz ~ 20kHz
- Pre-Set 40CH (2*20CH) Selectable Frequencies.
- Wireless System Adopts Intelligentized Cryptographic Hardware.
- IR Sync Downloading the Frequency from Receiver.
- Auto Frequency Scanning and Spectrum Display.
- Colorful TFT LCD Display and Menu Settings.
- Status of Frequency AF And RF Signal Etc.
- Up To 100 Meters Line-of-Sight Range.
- Auto Mute When Falling Down or Laid Down.
- Ideal for Professional Stage, Clubs, Music Entertainment Meeting, Training, Conference and karaoke Etc.
- Optional Hand-Held Microphone, Pocket Transmitter, Lavalier and Headset Available.

Specifications

System

Carrier Frequency	UHF 803.3 ~ 805.7MHz
Available Channels	40CH (2*20CH)
Bandwidth	2.6MHz
Dynamic Range	90dB
Total Harmonic Distortion	<0.5%
Frequency Response	30Hz ~ 20kHz ±2dB
Audio Output Level	1 x 6.3mm, 2 x XLR balance output

SU-890DR : Receiver

Power Supply	DC 12V-18V 1A
Consumption Power	3Watts
Signal/Noise Ratio	90dB
Receiving Sensitivity	-95dBm

SU-890HT : Handheld Transmitter

Carrier Frequency	UHF 803.3 ~ 805.7MHz
Bandwidth	2.6MHz
Frequency Switch	IR SYNC
Output Power	8mW / 30mW
Harmonic Radiation	<-50dBc
Battery Voltage	3V (2x1.5V AA Battery)
Battery Life	approx 8 hours

SU-890BT : Body-Pack Transmitter

Carrier Frequency	UHF 803.3 ~ 805.7MHz
Bandwidth	2.6MHz
Frequency Switch	IR SYNC
Output Power	8mW / 30mW
Harmonic Radiation	<-50dBc
Battery Voltage	3V (2x1.5V AA Battery)
Battery Life	approx 8 hours

Certifications : CE and RoHS

The SU-890D conforms to standard
 ETSI EN 300 422-1 , EN 62479: 2010 , EN 301 489-9
 IEC 60950-1:2005+A1:2009+A2:2013

● Specifications are subject to change without prior notification.