



Features

- * Conference system of discussion and voting functions.
- * One controller supports 128 units, expansion up to 4,096 units.
- * Four meeting modes: first-in/first out, normal, free and apply.
- * Speech microphone quantity selector: 1, 2, 4 & 6, chairman units are free of control.
- * All of the system are communicated through standard & secured 8 Pins conference system cable.
- * Three channel outputs for microphone units connection.
- * All of the equipments are connected hand-by-hand for easy wiring and maintenance.
- * Built-in a digital EQ for signal processor and noise delete.
- * Two line outputs for sound amplification system.
- * Voting and data management features could be done by link with PC where installed software.
- * Support 6 cameras by link together with auto-video tracking controller TS-0690.
- * Secure ground line protection from 8,000 volt static electricity.
- * Rack mount and tabletop design.
- * AC 120V or 220V, 50-60Hz operation.

Specifications

Model	TS-0604M
Description	Conference system controller
Power Supply	AC 120 or 220V; 50-60Hz
Power Consumption	10W
Max Power Consumption	350W
Output Power	110W/24V per channel
Aux Output	2V, 100 , unbalanced RCA type
Frequency Response	20-20KHz
S.N Ratio	>90dB
Total Harmonic Distortion	<0.1%
Overloading Distortion	1%
Crosstalk Attenuation	50dB
Connector	five 8 pin connector, two RS232 connectors and 8 pairs of RCA
Dimensions	484(L) x 305(W) x 88(H)mm
Weight	4.78kg
Finish	Black